

## PACKING SPECIFICATION

### Annodes: Packed in Cloth Bags of Compacted Backfill

1. **REQUIREMENTS:** These requirements are in addition to those listed in 9 CAT Specifications, material master descriptions, and Aramco Packing Specification 8314-0 and apply only to the materials indicated. Deviations from these requirements are not allowed without prior written approval from the Procurement Planner.
  - 1.1 Material master number items must be packed on skids and or pallets
    - 1.1.1 Prior to stacking the anodes on the skid/pallet, a tri-wall corrugated fiberboard sheet of the same length and width as the skid/pallet must be placed on the skid/pallet surface to provide an uninterrupted weight distribution base for the load.

The bagged anodes must be stacked in layers on the skid/pallet in a manner that enables the full length of each anode, including the cable, to be supported, without allowing any part of the anode to extend beyond the edge of the skid/pallet. The maximum permitted load height, including the skid/pallet, is 1,150 mm (45 inches).
  - 1.2 Each skid/pallet load must be:
    - 1.2.1 Covered by a cardboard cap and enclosed in water and ultraviolet (UV) resistant, heavy-duty polyethylene film (shrink-wrap, bag or suitable alternative).
    - 1.2.2 Firmly anchored by 4 metal straps of a minimum width of 18.75 mm (3/4 inch), two (2) per side.